

Overview

New levels of flexibility from the leading provider of open, Internet-enabled, automation infrastructure solutions

EasyIO is a suite of Niagara-based products designed to integrate diverse smart devices into a unified, Internet-enabled, web-based system. EasyIO solutions integrate LonWorks™, BACnet™, oBIX, Internet and web services protocols in a software platform that can be used in embedded controllers or server applications. EasyIO includes integrated network management tools to support the design, configuration, installation, and maintenance of interoperable networks.



The Niagara AX Supervisor® is a flexible network server used in applications where multiple EasyIO based JACE controllers will be networked together (SoftJACE®, EasyIO-J2, EasyIO-J6). The Niagara AX Supervisor serves real time graphical information displays to standard web-browser clients and also provides server-level functions such as: centralized data logging, archiving, alarming, real time graphical displays, master scheduling, system-wide database management, and integration with enterprise software applications. In addition, the Niagara AX Supervisor provides a comprehensive, graphical engineering toolset for application development.

oBIX is now included with the AX Supervisor as a means of integrating Niagara-based Release 2 JACEs. With release 2.3.522 or greater, the oBIX driver can be added to expose all data points, schedules, trends and alarms to a Niagara AX Supervisor. This oBIX driver is both a client and a server.

Features

- Java-enabled user interface (UI) as well as a non-Java UI for browsers.
- Supports an unlimited number of users over the Internet / Intranet with a standard web browser, depending on the host PC resources.
- Optional enterprise-level data archival using SQL, Oracle or DB2 database, and HTTP/HTML/XML text formats.
- “Audit Trail” of database changes, database storage and backup, global time functions, calendar, central scheduling, control, and energy management routines.
- Sophisticated alarm processing and routing, including e-mail and paging.
- Provides access to alarms, logs, graphics, schedules, and configuration data with a standard web browser.
- Password protection and security using standard Java authentication and encryption techniques with optional security supported via an external LDAP connection.
- HTML-based help system that includes comprehensive on-line system documentation.
- Supports multiple EasyIO-J2 and EasyIO-J6 stations connected to a local Ethernet network, or the Internet.
- Provides online/offline use of the Niagara Framework WorkPlace AX® graphical configuration tool and a comprehensive Java Object Library.
- Optional direct Ethernet based driver support for BACnet I/P, OPC (Client), Modbus TCP, and SNMP; additional point blocks for each driver may be purchased in blocks of 500 for each protocol.
- A “Small Building System” version is available for support of a system with up to three JACEs.

Platform Requirements

- **Processor:** Intel Pentium® IV, 2 GHz or higher
- **Operating System:** Microsoft Windows XP Professional, Windows 2003 Server (if Microsoft IIS is disabled), Vista Ultimate, Mozilla Firefox™ or Internet Explorer™ 5.0 or later
- **Memory:** 1 GB minimum, 2GB or more recommended for large systems
- **Hard Drive:** 1 GB minimum, 5 GB for applications that need more archiving capacity
- **Display:** Video card and monitor capable of displaying 1024 x 768 pixel resolution or greater
- **Network Support:** Ethernet adapter (10/100 Mb with RJ-45 connector)
- **Modem:** 56 KB minimum, full time high speed ISP connection recommended for remote site access (i.e. T1, ADSL, cable modem)



LonWorks is a trademark of Echelon Corp. BACnet is a trademark of ASHRAE. Java is a trademark of Sun Microsystems. Modbus is a trademark of Schneider Electric. Windows, Windows XP Professional, Windows Server 2003, Vista Ultimate and Internet Explorer are trademarks of Microsoft Corporation. Firefox is a trademark of the Mozilla Foundation. Pentium is a trademark of Intel Corp. Vykon, JACE, AX Supervisor and Niagara Framework are trademarks of Tridium, Inc. All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. Tridium, Inc. reserves the right to change or modify specifications without prior notice. The latest product specifications can be found by contacting our corporate headquarters, Richmond, Virginia. Products or features contained herein may be covered by one or more U.S. or foreign patents. © 2008 Tridium, Inc.

Ordering Information

Part Number	Description	Part number	Description
S-AX	Basic AX Supervisor; all JACEs must have EC-SP for connectivity to the AX Supervisor	Open system Drivers for AX Supervisor only (not for SBS)	
S-AX-SBS	Small Building System version of the AX Supervisor with a three JACE limit; all JACEs must have EC-SP for connectivity to the SBS AX Supervisor	DR-S-BAC-AX	Adds BACnet IP Client driver support to AX Supervisor; includes 500 points
S-AX-SBS-EXUP	Upgrade from the S-AX-SBS to a full AX Supervisor	DR-S-BAC-500	Adds 500 BACnet IP points to AX Supervisor with above driver option
Optional Database Drivers for External Database applications (not available for SBS version of AX Supervisor):		DR-S-MTCP-AX	Adds Modbus TCP driver support to AX Supervisor; includes 500 points
S-DB-SQL	Microsoft SQL Database Driver	DR-S-MTCP-500	Adds 500 Modbus TCP points to AX Supervisor with above driver option
S-DB-DB2	IBM DB2 Database Driver	DR-S-SNMP-AX	Adds SNMP driver support to AX Supervisor; includes 500 points
S-DB-ORCL	Oracle Database Driver	DR-S-SNMP-500	Adds 500 SNMP points to AX Supervisor with above driver option
S-AX-SBS-EXUP	Upgrade from the S-AX-SBS to a full AX Supervisor	DR-S-OPC-AX	Adds OPC Client driver support to AX Supervisor; includes 500 points
WP-AX	Additional copy of Workplace AX	DR-S-OPC-500	Adds 500 OPC points to AX Supervisor with above driver option
		DR-S-OBIX-AX	oBIX client for non-Niagara point data. Includes 500 points
		DR-S-OBIX-500	Adds 500 oBIX points to AX Supervisor

Typical Architecture

